

TC77^{ex}-NI

Touch Computer Datasheet



Your workers in the field need a mobile computer to communicate with others and to access information. Only in this way they can work with maximum efficiency and improve service to customers.

The TC77^{ex}-NI is the ultimate touch computer for your rugged environment and built to deliver the unstoppable performance you need. The TC77^{ex}-NI is built for the toughest conditions and certified to the strictest Ex safety standards for use in Zone 2 and Class I, II, III Div 2. This professional grade device married the intuitive and elegant smartphone experience with today's most advanced enterprise-class features. Your workers get everything they need to work smarter and faster, able to deliver the kind of service that will put your business a step above the competition. You get a ultra-rugged device built to last for years with everything you need to streamline your workflows and maximize your return on investment. Access to practically all information in your back-end systems wherever and whenever you need it. The ability to collect more types of data quicker than ever before. Immediate Push-to-Talk communication with field staff, line managers, despatch coordinators and colleagues in the office. 4G LTE support for robust, wireless connections in the fastest mobile phone networks in the world. And an extensive range of accessories which meets the unique demands of practically all mobile employees. The TC7X series – a simple way of equipping your field team with a true mobile office – now also in a potentially explosive atmosphere.

Explosion protection

Marking ATEX	Ex II 3G Ex ic op is IIC T5 Gc Ex II 3D Ex ic op is IIIB T100 °C Dc IP 64	Buttons	1 x on/off button 1 x function button 1 x scan button 2 x volume buttons (+/-) 4 x capacitive function buttons (home, menu, ESC, search function)
Certification	EPS 17 ATEX 1 028 X	External I/O	only for use outside potentially explosive atmospheres USB 2.0 High Speed (Host and Client) 1 x Cradle Connector (OTG host, data exchange and charging) 1 x Port (PoGo Pin) for 2-slot charger
Marking IECEx	Ex ic op is IIC T5 Gc Ex ic op is IIIB T100 °C Dc IP 64		
Certification	IECEx EPS 17.0012X		
Marking ETL	Class I Div. 2 Groups A, B, C and D Class II Div. 2 Groups F, G Class III; T4		
Certification	5012876		
	Other approvals and certificates, see bartec.com		

User environment

Operating temperature	-20 °C to +50 °C (-4 °F to 122 °F)	Barcode capture	SE4770-SR 1D/2D standard range imager Scan range at Code 39 barcode: 0.51 mm: 4.1 cm to 91.7 cm (0.02 inch: 1.6 inch to 36.1 inch) 0.08 mm: 7.6 cm to 14.7 cm (0.003 inch: 3.0 inch to 5.8 inch) supported symbologies/barcodes: see table
Storage temperature (without battery)	-40 °C to +70 °C (-42 °F to 158 °F)		ISO 14443 Type A and B; F; FeliCa and ISO 15693 cards; P2P mode and Card Emulation via Host; SAM support for Calypso, Felica and Mifare technology; Dual SAM support on TC77 SAM SKU
Relative humidity	5 % ~ 90 % (non-condensing)		
Protection class (IEC 60529)	IP 65 and IP 68		
Drop Specification	Multiple 2.4 m (94.5 inch) drop to concrete at room temperature MIL-STD-810G, Multiple 1.8 m (70.9 inch) drop to concrete across full operating temperature range		
Tumble Specification	2.000 tumbles from a height of 1.0 m (39.4 inch); meets and exceeds IEC tumble specification	Camera	Backside: 13 MP with autofocus Frontside: 5 MP fixed focus f/2.4 aperture; flash LED generates balanced white light; supports Torch mode; 4K video with image stabilization; Camera supports barcode scanning

Technical Data

Processor	Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz	Radio Frequency Band	Supports VoLTE, Carrier Aggregation up to 3DL CA AT&T FirstNet Ready certification Verizon PNTM certification LTE FDD: 700/800/850/900/1800/1900/AWS/2100/2600 (28,13,14,12,17/19,20/5,26/8/3/2,25/4,66/1/7); LTE TDD: 1900/2300/2500 (39/40/41,38); UMTS/HSPA/HSPA+: 850/900/AWS/1900/2100 (5/8/4/2/1); GSM/GPRS/EDGE: 850/900/1800/1900
Memory (RAM)	4 GB RAM	WLAN-WiFi	IEEE 802.11 a/b/g/n/ac/d/h/i/k/mc/r/v/w; Wi-Fi™ certified; IPv4, IPv6, 2x2 MU-MIMO
Mass storage	32 GB Flash pSLC		Data Rates 5 GHz: 802.11a/n/ac — up to 866.7 Mbps 2.4 GHz: 802.11b/g/n — up to 300 Mbps
Storage expansion	User accessible MicroSD - up to 32GB SDHC and up to 64 GB SDXC		Operating Channels Channel 1-13 (2412-2472 MHz); Channel 36-165 (5180-5825 MHz) Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies and bandwidths depend on regulatory rules and certification agency
SIM	2 Nano-SIM-Slots (Dual SIM, Dual Stand-by - EU Only)		Security and Encryption WPA3-Personal (SAE); WPA3-Enterprise; Enhanced Open - Based on opportunistic wireless encryption (OWE)*; WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP and AES) — EAP-TLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC and LEAP. EAP-PWD
Operating system	Android 11 with Mobility Extensions Security updates/patches on request		
Size (L x W x H)	161 x 84 x 28 mm (6.3 x 3.3 x 1.1 inch)		
Weight (with battery)	376 g (0.83 lb)		
Display	4.7", bonded		
Resolution	1280 x 720 pixels		
Front glass	Corning Gorilla Glass		
Touch function	Dual mode capacitive touch		
Usability	With Stylus or bare or gloved fingertip input		
Battery	Lithium polymer battery 3.7 V/4620 mAh (1S/2P) Battery change function Must only be changed and charged outside potentially explosive atmosphere.		
Notifications	Audible tone; multi-color LEDs; vibration		
Voice and audio	Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice		

* Note that OWE is a separate Wi-Fi Alliance certification program and not WPA3

Multimedia	Wi-Fi Multimedia™ (WMM) and WMM-PS
Features	Soft AP, 2x2 MU-MIMO, 256 QAM Modulation on 5G GHz radio; Maximum Ratio Combining (MRC), Tx/Rx Low-Density Parity Check (LDPC), Transmit Beamforming(TxBF) and Beamformee (BFee) capability, Full IEEE 802.11 a/b/g/n legacy compatibility
Certifications	WFA (802.11n, WMM-PS, 801.11ac, PMF)
Fast Roam	PMKID caching; Cisco CCKM; 802.11r; OKC
Bluetooth	Bluetooth v5.0, Class 2, Bluetooth Low Energy (BLE)
GPS	Autonomous, Assisted GPS (A-GPS); Navstar; GLONASS; Galileo; BeiDou
Software	No functional changes were made to the device due to the explosion protection. All tools and applications available from Zebra for the TC77 are compatible with the TC77 ^{ex} -NI version. e.g. messaging via Workforce Connect PTT Express or the Mobility DNA solutions from ZEBRA
Mobility DNA	Mobility DNA solutions help you get more value out of our mobile computers by adding functionality as well as simplifying deployment and management of our mobile devices. For more information on these Zebra-only features, please visit www.zebra.com/mobilitydna
PTT (Push-to-Talk) App	Powered by Zebra Technologies, BARTEC brings the enterprise-class push-to-talk application PTT Pro into hazardous areas. PTT Pro connects your workforce with enterprise-class instant PTT and secure messaging services. It supports direct messaging, image, audio, and video - regardless of whether your users are carrying a BARTEC mobile device in hazardous areas, or their own Android or Windows device in non-hazardous areas. For more information see bartec.com
Warranty	1 year
Service contracts	COMFORT and ALL-IN
Scope of delivery	Touch Computer TC77 ^{ex} -NI Battery Hand strap Quick Start Guide
Also required	(not included in the delivery) Base station or battery charging station for charging

Accessories

see datasheet: TC77^{ex}-NI Accessories

It is absolutely necessary to use original accessories from BARTEC!

Supported Symbologies / Barcodes

1D/Linear Symbol/Codes	Code 11 Code 39 Code 93 Code 128 Codabar Coupon Code Chinese 2 of 5 Discrete 2 of 5 EAN-8 EAN-13 Interleaved 2 of 5 MSI UPCA UPCE UPC/EAN supplementals Trioptic 39 RSS-14 RSS Expanded RSS Limited Webcode
2D Stacked and 2D Matrix Symbol/Codes	Aztec Australian 4-state Canadian 4-state Composite AB Composite C PDF-417 Data Matrix Dutch Kix Japanese 4-state Macro PDF-417 (Macro) Micro PDF-417 Micro PDF-417 microQR Maxi Code QR Code TLC39 UK 4-state US Planet US Postnet USPS 4-state (US4CB)

Ordering information

TC77 ^{ex} -NI with 4G/LTE US+ CANADA	B7-A264-1K5333311300
TC77 ^{ex} -NI with 4G/LTE Rest of the world	B7-A264-1L5333311300

BARTEC GmbH

Max-Eyth-Str. 16
97980 Bad Mergentheim

Tel.: +49 7931 597 0
Fax: +49 7931 797 119

Mail: info@bartec.com
Web: bartec.com

Technical data subject to change without notice.